

FEATURES

STANDARD



USED BY:

- AUTOMOTIVE ASSEMBLY PLANTS
- AEROSPACE
- SHIPYARDS
- STEEL PLANTS
- MILITARY
- COMPONENT MANUFACTURERS
- LOGISTICAL MANAGEMENT
- INDUSTRY

IDEAL FOR:

- AUTOMOTIVE ASSEMBLY PLANTS
- AEROSPACE
- SHIPYARDS
- STEEL PLANTS
- MILITARY
- COMPONENT MANUFACTURERS
- LOGISTICAL MANAGEMENT
- INDUSTRY

SOFTWARE



OPTIONAL:



METAL EMBOSSEYER SERIES

ME 1000 - 2000 2D DATA MATRIX



IDEAL FOR LONG LIFE INDUSTRIAL MARKING APPLICATION

2D MATRIX BARCODE DURABLE EMBOSSED METAL PLATES

- ✓ Ideal for harsh post marking treatment of tags like sanblasting, painting etc.
- ✓ PVC or Mylar tags need to be regularly replaced causing lost time, identification error and high consumables costs.
- ✓ Tags are required to have a long working life and will be subjected to enviromental degradation
- ✓ Application where marking the component or items directly:
 - affect its mechanical integrity
 - is too difficult to achieve
 - is too costly (laser dot peen)
 - too time consuming affecting production efficiency



TECHNICAL FEATURES

2D ENCODING AREA

ECC200 BARCODING		
Row & col.	Nuber only	Alphanumeric
10x10	6	3
12x12	10	6
14x14	16	10
16x16	24	16
18x18	36	25
20x20	44	31
22x22	60	43
24x24	72	52
26x26	88	64

**Total area depends on dot size*




Plate dimension in mm. Dashed area not usable



2D Data Matrix Barcode Reader
DNR-7500V-00
CIM P/N C7010972

ME1000
2D Data Matrix

ME2000
2D Data Matrix



PLATE & FEEDER

dimensions

width: 30 ÷ 115 mm / 1.18 ÷ 4.53 in
height: 21 ÷ 90 mm / 0.83 ÷ 3.54 in

thickness

0.4 ÷ 0.9 mm / 0.0157 ÷ 0.0354 in

materials

stainless steel, carbon steel, aluminium, copper and brass

input hopper

ME1000 2D Data Matrix: manual feed - single access point

ME2000 2D Data Matrix: up to 250 plates capacity. (Ø 0,4 mm/0.0157 in)

output hopper

ME1000 2D Data Matrix: manual feed

ME2000 2D Data Matrix: up to 250 plates capacity. Options: FIFO (first in - first out) technology or side eject.

STAMPING

technology

standard alphanumeric marking plus 2D matrix embossing

Reed - Salomon error correction

drum capacity

60 or 90 slots - 45 slots drum available for special applications

type set

many characters configuration available: 2D dot font: 0,25 / 0,50 / 0,75 mm

indenting

Simplex 2, OCRB1, BlockUSA, Double Block, etc. Height 3 ÷ 12 mm / 0.118 ÷ 0.472 in.

debossing

Elite Dog Tag

stamping area

full plate except for 1 mm / 0.039 in from the top and left/right edges and 7 mm / 0.28 in from the bottom edge. Avoid edges in order to not damage the stylus.

2D embossable area

See table beside (2D ENCODING AREA)

performance

Plate types	Card production time	Production time
18x18: 23 alphanumeric char. data	49.6" each plate (32" for 2D)	72 cph
16x16: 5 numeric char. data	40.0" each plate (26.8" for 2D)	90 cph
14x14: 5 numeric char. data	32.8" each plate (20" for 2D)	110 cph

COMMUNICATION INTERFACE & SOFTWARE

communication interface

RS232 serial port

Isolated USB to RS232 converter

operating system

Compatible with Windows 7/8/10

application software

PowerTag 2D Data matrix - PC application proprietary software compatible with CIM 2D Data to Barcode automatic conversion. Automatic data field; plate archive; DBIII, DBIV, Excel, MS Access file compatibility; self diagnostic, automatic repetition of faulty plate personalization, resettable and non-resettable counters.

protocol

CIM, Xon-Xoff, MultiEmbosser, Stored Format default, Stored format Select and Pound-Pound via external keyboard; 20 storable formats downloadable

LCD Edit

ECC200

2D Matrix encoding

ECC200

HARDWARE

power supply

100 - 117 - 220 - 230 o 240 Volt - 50 o 60 Hz

power consumption

800 Watt

operating environment

temperature: 5 ÷ 40° C / 41 ÷ 104 °F

relative humidity: 30% ÷ 90% non condensing

dimensions (WxDxH)

630 x 740 x 380 mm / 24.8 x 29.1 x 15 in

weight

ME1000 2D Data Matrix - 75 Kg / 165 lbs - ME2000 2D Data Matrix - 78 Kg / 172 lbs

VARIOUS

LCD display

2 lines of 40 characters LCD display for diagnostics and offline operation

Others

lithium back up battery; security operation with key lock; emergency stop red button, machine status indicator lights, nearend input / near full output hopper plate sensor for continuous production (ME2000 2D Data Matrix)

Easy & flexible: manual (**ME1000 2D Data Matrix**) or automatic (**ME2000 2D Data Matrix**) loading and unloading has never been easier. Equipped with a unique clamp for plates of most dimensions and metals. **CIM** has developed various command protocols allowing the ME1000 / 2000 2D Data Matrix to easily interface with custom applications.



cim-usa.com